

C | 4i

- y | ä ä 93.0%
- y ¶ ä!ÿß v8 gÉ ä h
- y U* y~2-ÿß v
- y 32° Oò
- y ... a' y [% 4kV, » % 6kV
- y ¶•y' y " k 9' k?è'
- y 9 IP67 y UL tDÓ kBx~C Ú J ê Ë
- y Class 2 & SELV
- y U 9 è Class I, Division 2 .•«`

C | 5 é




EUB-096SxxxST ©ç 96W vU²Ü ~D}k¿ÿµ 98 90-305Vac k ÀÄÝä
 ä œ fož 4©çD}© WJs°kd°°C ¿Áç^• ò—œžÝä |äk-Ø ÛÓ—‹k'ñ
 •½kâÝªUä4D} U´Ákw•x4D} .xož¶•y' k ,...ª' o• 9' o•?
 è' C " k¾©'š44.D} —žl ðož

1 Y æ =

ÎPÔW T•ÿ	µ´ÎP ÔWÿ(1)	ÎPÔW -þš	Î´Ô8 ÿ(2)	ÎPÔ8 ÿ	£ÛÎP ´]´ (3)	´)d		1Y
							120Vac	220Vac	
700-1050mA	700-1050mA	700 mA	90~305 Vac/ 127~300 Vdc	48~137Vdc	96 W	93.0%	0.99	0.96	EUB-096S105ST
1400-2100mA	1400-2100mA	2100 mA	90~305 Vac/ 127~300 Vdc	24 ~ 69Vdc	96 W	92.0%	0.99	0.96	EUB-096S210ST ⁽⁴⁾
2625-3500mA	2625-3500mA	2800 mA	90~305 Vac/ 127~300 Vdc	14 ~ 36Vdc	96 W	91.5%	0.99	0.96	EUB-096S350ST ⁽⁵⁾

- l u g1 h9 = ¶ ä ÄÝÿß v8
- g2 hUL, FCC •š 98 y <GI ê <JI! ¿Uy <GI127-250Vdc g" KSh
- g3 h y i Ú^y 220Vac g!•†•" h
- g4 h SELV ÿß
- g5 h Class 2 & SELV ÿß

I-V V € ¼



Î 4ì x

Input Voltage (V)	Input Frequency (Hz)	Input Power (W)	Input Current (A)	Output Voltage (V)
90 Vac	-	-	-	127~300 Vdc
47 Hz	-	-	-	
-	-	0.75 MIU	-	UL8750; 277Vac/ 60Hz
-	-	0.70 mA	-	IEC60598-1; 240Vac/ 60Hz,
-	-	1.10 A	-	100% 120Vac
-	-	0.65 A	-	100% 220Vac

Î 4î x

¿ d	£ 3 š	À 1 š	£ Ü š	Ô I
I ² t	-	-	1.30 A ² s	220Vac 25 10%l _{pk} -10%l _{pk} =640 µs
	0.90	-	-	100-277Vac, 50-60Hz, 70%-100% (67-96W)
	-	-	20%	
	-	-	10%	220-240Vac, 50-60Hz, 75%-100% (72-96W)

Î Þ4î x

¿ d	£ 3 š	À 1 š	£ Ü š	Ô I
	-5%loset	-	5%loset	100%
(loset) EUB-096S105ST EUB-096S210ST EUB-096S350ST	700 mA 1400 mA 2625 mA	- - -	1050 mA 2100 mA 3500 mA	
EUB-096S105ST EUB-096S210ST EUB-096S350ST	700 mA 1400 mA 2625 mA	- - -	1050mA 2100mA 3500mA	
(pk-pk)	-	5%l _{omax}	10%l _{omax}	100% 20 MHz BW
	-	-	10%l _{omax}	100%

EUB-096S105ST

P á é

¿ d	£ 3 š	À 1 š	£ Ü š	Ô I
@120Vac EUB-096S105ST Io=700 mA Io=1050 mA EUB-096S210ST Io=1400 mA Io=2100 mA EUB-096S350ST Io=2625 mA Io=3500 mA	88.5% 87.0% 87.5% 86.5% 87.5% 86.0%	90.5% 89.0% 89.5% 88.5% 89.5% 88.0%	- - - - - -	100% 25° 2%
@220Vac EUB-096S105ST Io=700 mA Io=1050 mA EUB-096S210ST Io=1400 mA Io=2100 mA EUB-096S350ST Io=2625 mA Io=3500 mA	91.0% 89.5% 90.0% 89.0% 89.5% 88.5%	93.0% 91.5% 92.0% 91.0% 91.5% 90.5%	- - - - - -	100% 25° 2%
@277Vac EUB-096S105ST Io=700 mA Io=1050 mA EUB-096S210ST Io=1400 mA Io=2100 mA EUB-096S350ST Io=2625 mA Io=3500 mA	91.5% 90.0% 90.0% 89.0% 90.0% 89.0%	93.5% 92.0% 92.0% 91.0% 92.0% 91.0%	- - - - - -	100% 25° 2%
	-	355,000 Hours	-	220Vac, 25 , 80% (MIL-HDBK-217F)
	-	77,000 Hours	-	220Vac 80% 70
	-40°C	-	+89°C	
	-40°C	-	+75°C	
	-40°C	-	+85°C	: 5%RH to 100%RH
(L x W x H) (L x W x H)	6.03 x 2.37 x 1.44 153 x 60 x 36.5			6.85 x 2.37 x 1.44 174 x 60 x 36.5
	-	730 g	-	

I u

25°C

μ 0 Â x 0

μ ù ç	x 0
UL/CUL	UL 8750, UL 1310, CAN/CSA-C22.2 No. 250.13, CAN/CSA-C22.2 No. 223-M91
CE	EN 61347-1, EN61347-2-13
KS	KS C 7655
+ 3 / x 0	0 I
EN 55015 ⁽¹⁾	Conducted emission Test & Radiated emission Test
EN 61000-3-2	Harmonic current emissions
EN 61000-3-3	Voltage fluctuations & flicker
FCC Part 15 ⁽¹⁾	ANSI C63.4 Class B
	This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: [1] this device may not cause harmful interference, and [2] this device must accept any interference received, including interference that may cause undesired Operation.
EMS x 0	0 I
EN 61000-4-2	Electrostatic Discharge (ESD): 8 kV air discharge, 4 kV contact discharge

` › • Ž

- w * Ò t • Ž

_ f • Ž

]´•Ž

EUB-096S105ST(lo=700mA)

EUB-096S105ST(lo=1050mA)

EUB-096S210ST(lo=1400mA)

EUB-096S210ST(lo=2100mA)

EUB-096S350ST(lo=2625mA)

EUB-096S350ST(lo=3500mA)

ˆ › d • Ž

5 f G á • Ž

• ã x

? d	Ô I

Î P Ô W \ Y Ô x — f ´

● EUB-096S105ST

Î P Ô W f ´ (loset)	Î P Ô 8 Ỹ		Ô I
À 1 š	£ 3 š	£ Ü š	
1050mA	48V	91.5V	
1000mA	48V	96V	
950mA	51V	101V	
900mA	53V	106V	
850mA	57V	113V	
800mA	60V	120V	
750mA	64V	128V	
700mA	69V	137V	

● EUB-096S210ST


Î P Ô W f ´ (loset)	Î P Ô 8 Ỹ		Ô I
À 1 š	£ 3 š	£ Ü š	
2100mA	24V	46V	
2000mA	24V	48V	
1900mA	26V	50.5V	
1800mA	27V	53V	
1700mA	29V	56.5V	
1600mA	30V	60V	
1500mA	32V	64V	
1400mA	35V	69V	

● EUB-096S350ST

Î P Ô W f ´ (loset)	Î P Ô 8 Ȳ		Ô I
À 1 š	£ 3 š	£ Ü š	
3500mA	14V	27.5V	
3325mA	15V	28.5V	
3150mA	16V	30.5V	
2975mA	16V	32V	
2800mA	17V	34V	
2625mA	18V	36V	

I u IP67

2 Ä ç



T_ 8 U . Y L -

RoHS

2011/65/EU

EU 2015/863

' [b ç

' X • N	• -	' X 5 é		
		• ù	Q	è
2016-07-28	A		/	/
2019-08-14	B			
		/	50-60Hz	
			UL/CUL	
			KS	
			FCC	
			EN 61000-4-5	
			/	
	RoHs	/		